

## SMD COMPONENT COUNTING


The County adaptor for counting taped SMD components is an optional accessory (8301.018), allows the counting of the SMD components through the holes of the support tape.

Extraction hole

The worktop 8301.027 includes two easy insertions pins with adjustable clutch. Furthermore, at least one handle (8301.030) is required for rewinding the reels. The aluminum empty reel (8301.021) is an available optional to speed up the counting operations and subsequent rewinding of the SMD components

## **AXIAL AND RADIAL PTH COUNTING**

Before counting it is necessary to select the lead component number by setting the divider. For bandolier counting the 8301.023 support is available, with an easily inserted 8301.025 handle (see figure on right)



PRESET mode counting (with audible allarm when the desired component number is reached)

Calibration test and self diagnostic procedure Last counting value ane condition memory

Models 8301.082 and 8301.084 with rechargable battery, Barcode reader input, output for printer/PC, Watch, Datalogger with 500 counting record

Maximun countig value: 999999 comp.

Minimun lead diameter (PTH component): 0,4 mm Axial component bandolier width (PTH): 55 - 110 mm Radial component bandolier width (PTH): max 18 mm Maximun component diameter (PTH): 14 mm

Maximun tape height (SMD component): 56 mm

Display: 4 digits 13 mm height

Dimensions: 240 x 130 x 110 mm - Weight 1,8 kg

8301.081 County EVO 230V/50-60Hz

8301.082 County EVO 230V/50-60Hz with accumulator, barcode input, printer output, watch

8301.083 County EVO 115V/50-60Hz

8301.084 County EVO 115V/50-60Hz with accumulator, barcode input, printer output, watch

8301.350 ISO9000 traceable certificate

## Accessories for counting of PTH taped component

8301.023 Complete support for rolled bandolier

8301.025 PTH Bandolier handle

## Accessories for counting of SMD taped component

**8301.018** SMD Adaptor

8301.027 Worktop with 2 pins for reel

8301.030 SMD Reel handle

8301.021 Empty Reel aluminium made for County-EVO

Barcode e Printer (photos and specifications at page 4)

8301.155 Barcode with coiled cord

8301.095 Direct thermal label printer

8301.096 57x51mm 1360 labels/roll